


Klauke

UAP332 32kN Battery Powered Hydraulic Pressing Machine



Technical data

Linear force	32 kN
Weight	3.6 kg
Dimensions	359 x 76 x 325 mm
Ambient temperature	-10 °C up to 40 °C
Battery	18 V, Li-Ion
Battery charger	230 V (110 V on request)
Number of pressings	Approx. 400 (NS 20 / 4.0 Ah battery)
Pressing jaw holder	rotates 350°
Bluetooth	•
Realtime clock	•
OLED display	•
Hydraulic Pressure Control	•

suitable for

SB pressing jaw Standard 32 kN




- Stainless steel, steel: max. NS 54 mm / 2"
- Copper, copper alloys: max. NS 54 mm / 2"
- Multi-layer pipe / PEX pipe: max. NS 50 mm / 2"
- The stated information is system-dependent













QC pressing chain Quick-Click 32 kN



- Can be used only in connection with adapter jaw SBKQC (not included in scope of supply)
- Stainless steel, steel: max. NS 54 mm / 108 mm / 4"
- Copper, copper alloys: NS 54 mm / 108 mm / 4"
- Multi-layer pipe / PEX pipe: max. NS 110 / 4"
- The stated information is system-dependent.

Jaw/Machine Compatibility



		MAP215	MAP219	UAP332	UAP432
	SBM	•			
	UWM	• in connection with WE			
	SBMX		•		
	UWMX		•		
	SB			•	•
	UW			•	•
	WE	•	•	•	•
	SBKQC			•	•
	SB- KUAP4				•
	QC			• in connection with SBKQC	• in connection with SBKQC
	SSK			• in connection with SBKQC	• in connection with SBKQC
	BP ... LP				• in connection with SBKUAP4