


Klauke

MAP215

15kN Battery Powered Hydraulic Pressing Machine



Technical data

Linear force	15 kN
Weight	1.7 kg
Dimensions	404 x 80 x 118 mm
Ambient temperature	-10 °C up to 40 °C
Battery	18 V, Li-Ion
Battery charger	230 V (110 V on request)
Number of pressings	Approx. 150 (NS 20 / 1.5 Ah battery)
Pressing jaw holder	rotates 350°
Bluetooth	•
Realtime clock	•
OLED display	•
Hydraulic Pressure Control	•


suitable for













SBM pressing jaw Mini 15 kN



- Stainless steel, steel: max. NS 22 mm (NS 28 mm on request) / 3/4"
- Copper, copper alloys: max. NS 28 / 1"
- Multilayer pipe / PEX pipe: max. NS 32 mm / 1-1/4"
- The stated information is system-dependent.

Jaw/Machine Compatibility



		MAP215	MAP219	UAP332	UAP432
	SBM	•			
	UWM	• in connection with WE			
	SBMX		•		
	UWMX		•		
	SB			•	•
	UW			•	•
	WE	•	•	•	•
	SBKQC			•	•
	SB- KUAP4				•
	QC			• in connection with SBKQC	• in connection with SBKQC
	SSK			• in connection with SBKQC	• in connection with SBKQC
	BP ... LP				• in connection with SBKUAP4